

Excellent Grip Properties Heavy Duty Epoxy Coating with Customizable Color and Anti-Slip Aggregate

Our Product Introduction

for more products please visit us on epoxyresinfloorcoating.com

Basic Information

- Certification: ISO14001, CCC, RoHS, ISO9001
- Minimum Order Quantity: 100
- Price: 3.5




Product Specification

- Model NO.: CK-SL5001
- Color: Customized
- Appearance: Liquid
- Main Material: Epoxy
- Application Method: Roller
- Drying Method: Air Drying
- Substrate: Cement Base
- Mix Ratio: 5:1 By Weight
- Shelf Life: 12 Months
- Finish Type: High Gloss
- Package Specification: 20Kg/Bucket
- Density: 1.3g/cm³
- Hardness: 3H
- Pot Life: 30-40mins@25°C
- Curing Time: 8-10hrs@35°C, 15-20hrs@25°C



More Images



Product Description

Excellent Grip Properties Epoxy Resin Anti-Slip Coating with Heavy Duty Aggregate

Epoxy Floor Coatings provide a fast-drying, tough, and protective coating for concrete, metals, and other materials, offering resistance to chemicals such as acids. This makes epoxy suitable for floors exposed to medium and heavy loads in storage areas, warehouses, and production facilities. When used in flooring applications, epoxy coatings create durable, long-lasting solutions with decorative, high-gloss finishes available in various colors.

Key Features:

- Seamless, high gloss finish
- Resistant to stains and water
- Durable, tough, and strong construction
- Fast application with 24-hour cure time
- Easy to clean and maintenance-free
- Withstands heavy use and mechanical loads

Product Advantages:

Epoxy flooring is ideal for environments requiring resistance to extreme temperatures, foot and machine traffic, chemicals, oil, and other fluids without peeling or corrosion. Its seamless, poured application eliminates joints and ridges found in tile flooring, creating a more sanitary surface without cracks for dirt and bacteria accumulation. The smooth surface facilitates easy movement of hospital gurneys and forklifts.

Technical Specifications:

Item	Epoxy Resin(A)	Epoxy Hardener(B)
Appearance	Liquid	Liquid
Color	Custom Colors	Clear
Density@25°C	1.3g/cm3	
Mix Ratio	5:1 by weight	
Hardness	3H	
Pot Life	30-40mins@25°C	
Curing Time	8-10hrs@35°C, 15-20hrs@25°C	
Recoat Time	2Hrs	
Thickness	1-3mm	
Shelf Life	12 Months	

Application:

Epoxy coatings are normally applied over concrete floors to provide high-performance, smooth, and durable surfaces that withstand heavy loads. Industrial sites, warehouses, and commercial buildings rely on epoxy floors to maintain clean and safe conditions for workers, equipment, and inventory.

Company Profile

Established in 1993, Guangdong Crekoat New Materials Co., Ltd. was formed by epoxy resin industry experts to meet growing demand for quality resin products. Our growth has made us one of China's leading suppliers of epoxy resin products.

With two factories in Foshan and Dongguan covering 20,000m² and annual output of 1,000,000 tons, we feature advanced production equipment, precise testing instruments, and strict quality assurance systems. We are ISO9001 and ISO14001 certified, with over 20 years' experience producing epoxy resin coatings that meet SGS and RoHS environmental standards.

Frequently Asked Questions

Q1: Are you a manufacturer or what else?

A1: We are a professional epoxy resin manufacturer since 1993, located in Dongguan, China.

Q2: May I get the sample first?

A2: Yes, you can. Sample cost should be paid by buyer. We will offer best price for you.

Q3: What is the minimum order quantity for this product?

A3: MOQ is 100KGS. We also can support trial order and sample order.

Q4: May I have my own logo on the product?

A4: Yes, we accept OEM, which both are available for label, package and logo.

Q5: How many days will you deliver the products?

A5: Generally it will take 3-7 days to produce the products.

Q6: Will the Crystal Clear Epoxy Resin turn yellow over time?

A6: No, because we add HALS, which is UV protection, it won't change yellow.

Q7: Does this Crystal Clear Epoxy Resin tend to scratch over time?

A7: Our product is Scratch Resistance, Heat Resistance, Electrical resistance.

Q8: How long can last if it is not mixed?

A8: The shelf life is about 12 months, Sealed storage required.



Guangdong Crekoat New Materials Co., Ltd.



+8615017402317



info@crekoat.com



epoxyresinfloorcoating.com

No.38, Fengguo Industrial Avenue, Sanshui District, Foshan City, China